

RV-US3-S

Standard Undersink Filter with Sediment Prefilter



Designed for Developing Markets



- Sealed construction unit with 12,000 gallon capacity
- KDF® / GAC Filter Media
- 6-stage filtration and purification system
- Sediment prefilter cartridge removes sediments with hypoallergenic multi-micron filtration
- Installed under the sink, out of sight
- Connects to separate, chromed, long-reach faucet
- Includes easy-installation kit
- Quick connect fittings for simple installation / replacement
- Available inline for direct connection to faucet
- Bacteriostatic media: prevents bacteria growth (algae, fungi)
- Improves taste and color, eliminates odors
- Reduces most EPA listed contaminants
- Includes prorated warranty

Installation kit includes 6 feet of tubing (1/4" outside diameter), saddle valve, long-reach faucet, fittings and adapters.



Housing bracket included



Max Capacity	12,000 gallons (45,425 liters)
Recommended Flow	1.0 gpm (3.8 lpm)
Unit Height	13.5" (34.3 cm)
Unit Width	11" diameter (27.9 cm)
Unit Box Dimensions	11" x 18" x 7" (27.9 x 45.7 x 17.8 cm)
Unit Shipping Weight	8.1 lbs (3.7 kg)
Packing	4 per master case
Master Dimensions	23" x 13" x 14" (58.4 x 33 x 35.6 cm)
Master Case Weight	35 lbs (15.9 kg)

H₂O International Inc.
3001 SW 15th St. - Suite C
Deerfield Beach, FL 33442 1
800 570-3464 USA Toll Free
1 954 570-3464 International
info@h2ofilter.com
www.h2ofilter.com

