











# ICF/ISF SERIES

Inline Filters  
Data Sheet



ICF-10



ISF-10

## Chlorine Taste & Odor Reduction - ICF-10 | ICF-10Q | ICF-10Q38

Coconut Shell Carbon	
Service Life	1 yr or 2000 gal (7570 L)
Maximum Flow	.50 gpm (1.9 lpm)
Maximum Pressure	125 psi (8.6 bar)
Maximum Temperature	100 °F (38 °C)
Minimum Temperature	35 °F (2 °C)

### Materials of Construction

Shell:	Polypropylene
Media:	Coconut Shell Carbon
Inner Pads:	Polypropylene

### Available Port Sizes

- 1/4" Female NPT Basic
- 1/4" Quick Connect
- 3/8" Female NPT Basic
- 3/8" Quick Connect

**WARNING:** Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

### Distributed by:



**1-800-451-1111**

**Toll-Free Number - - -**

**International - - -**

an a ture b roni ater Te nolo

## Dirt & Sand Reduction - ISF-10 | ISF-10Q

Service Life:	Applications vary
Maximum Flow:	.50 gpm (1.9 lpm)
Maximum Pressure:	125 psi (8.6 bar)
Maximum Temp:	100 °F (38 °C)
Minimum Temp:	35 °F (2 °C)
Micron Rating:	5M

### Materials of Construction

Shell:	Polypropylene
Media:	Polypropylene

### Applications

- Ice makers
- Reverse osmosis systems
- Water Coolers
- Coffee makers
- Refrigerators