

# PRESSURIZED TANKS

## RO SERIES

### STORAGE TANKS



This tank is tested and certified by NSF International against ANSI / NSF Standard 58 for material requirements only.

#### COMPONENT

**AQT™ Storage Tanks** are NSF approved under Standard 58 and CE approved under the PED (Pressure Equipment Directive). Through these approvals our tanks carry the appropriate markings and can be used anywhere in the world.

**AQT™ Storage Tanks** have Stainless Steel connections to prevent lead contamination. Its high grade butyl diaphragm and polypropylene liner are made with materials approved by the FDA to ensure water of the highest quality.

#### TANK SPECIFICATIONS

- |                          |                 |              |                      |
|--------------------------|-----------------|--------------|----------------------|
| • Max. Working Temp:     | 104° F (40° C)  | • Diaphragm: | High Grade Butyl     |
| • Max. Working Pressure: | 100 psi (7 bar) | • Liner:     | Virgin Polypropylene |
| • Preloaded Air:         | 7 psi (0.5 bar) |              |                      |

#### FEATURES

- |   |  |
|---|--|
| • Base Included                         | • Certified to NSF/ANSI Standard 58      |
| • 304 Stainless Steel Connections       | • High Grade, Heavy Duty Butyl Diaphragm |
| • Pre-Charged Tanks                     | • Material Approved by FDA               |
| • Triple Coated High Grade Baked Enamel | • Side Stainless Steel Air Connector     |





# RO SERIES

## STORAGE TANKS

\* The volume above is total capacity, not water storage volume.

RO SERIES - SPECIFICATIONS											
PART NUMBER	DESCRIPTION	CONNECTION	COLOR	DIAMETER		HEIGHT (With Base)		VOLUME		WEIGHT (Shipping Box)	
				in	cm	in	cm	gal	L	lbs	kgs
RO-0.5-W14	0.5 Gallon Tank	1/4" NPT	White	5.5	14	7.9	20	0.5	3	2.5	1.1
RO-2.0-W14	2.0 Gallon Tank	1/4" NPT	White	8	20.3	11.5	29.2	2	8	4.8	2.2
RO-3.2-W14	3.2 Gallon Tank	1/4" NPT	White	9	22.9	13.7	34.8	3.2	12	6.8	3.1
RO-4.5-W14	4.5 Gallon Tank	1/4" NPT	White	11	28	13.8	35.1	4.5	18	8	3.6
RO-4.5-B14	4.5 Gallon Tank	1/4" NPT	Blue	11	28	13.8	35.1	4.5	18	8	3.6
RO-4.5-BLK14	4.5 Gallon Tank	1/4" NPT	Black	11	28	13.8	35.1	4.5	18	8	3.6
RO-6.0-W14	6.0 Gallon Tank	1/4" NPT	White	11.4	29	15.7	40	6	24	10.2	4.6
RO-9.2-W14	9.2 Gallon Tank	1/4" NPT	White	11.4	29	21.7	55	9.2	40	14.8	6.7
RO-14-B14	14 Gallon Tank	1/4" NPT	Blue	15.3	39	22.4	56.4	14	60	23.7	10.8
RO-14-B34	14 Gallon Tank	3/4" NPT	Blue	15.3	39	22.4	56.4	14	60	23.7	10.8
RO-14-W14	14 Gallon Tank	1/4" NPT	White	15.3	39	22.4	56.4	14	60	23.7	10.8
RO-14-W34	14 Gallon Tank	3/4" NPT	White	15.3	39	22.4	56.4	14	60	23.7	10.8
RO-20-B34	20 Gallon Tank	3/4" NPT	Blue	15.3	39	31	78.8	20	80	27.8	12.6
RO-20-W34	20 Gallon Tank	3/4" NPT	White	15.3	39	31	78.8	20	80	27.8	12.6
RO-28-W10	28 Gallon Tank	1" NPT	White	16.9	43	30.1	76.5	28	100	34.1	15.5
RO-44-W114	44 Gallon Tank	1 1/4" NPT	White	21.7	55	36.4	92.5	44	160	59	26.8



- 304 Stainless Steel Water Connection
- Water Chamber
- High Grade Heavy Duty Butyl Diaphragm
- FDA Grade Polypropylene Liner
- Triple Coated High Grade Baked Enamel



Base Included



Distributed by: H<sub>2</sub>O International Inc.



3001 S.W. 15th Street, Suite C, Deerfield Beach, FL 33442

sales@h2ofilter.com • www.h2ofilter.com

**Toll-Free Number:** 1-800-570-3464

**International:** 1-954-570-3464

Manufactured by Hydronix Water Technology